

POLYFLOR KUDOS WOOD PU

- Captures the natural beauty of wood
- Authentic reproductions of real materials
- Borders, corners and feature strips available in a variety of formats and different colour combinations upon request

SPECIFICATION



2.5mm



0.55mm



36 @ 101 x 914mm = 3.34m²



4290g/m²



GENERAL PERFORMANCE
EN 649



REACTION TO FIRE
EN ISO 13501-1 Class Bfl-S1 { EN/AS ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass
ASTM E662 <450
ASTM E648 Class 1



SLIP RESISTANCE
EN 13893 Class DS (dry condition)*
DIN 51130 R9
AS/NZS 4586 R9



ABRASION RESISTANCE
EN 649 Group T



INDENTATION - RESIDUAL
EN 433 ≤ 0.1mm



DIMENSIONAL STABILITY
EN 434 ≤ 0.25% max.



CASTOR CHAIR (continuous use)
Suitable



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor Kudos PU achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429) in major use areas such as education, healthcare and retail. Kudos PU is 100% recyclable and contains 15% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



APPLICATIONS
Kudos PU is ideal for all residential areas and heavy commercial areas such as offices, schools, hospitals and public buildings.



Suitable for underfloor heating Max. 27°C
For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.
At the date of issue the data presented is correct.
* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2006




POLYFLOR
KUDOS

WOOD

PERFORMANCE AND
PROPERTIES

A+BRE
ENP 429
ENVIRONMENTAL
RATING
Refer to BRE Global ratings
on www.greenbooklive.com



POLYFLORTM
COVERING THE WORLD