

POLYFLOR BEVEL LINE STONE PU

- Captures the natural beauty of stone
- Authentic reproductions of real materials
- Design accessories available upon request

SPECIFICATION



2.5mm



0.7mm



bevelled edges



457 x 457mm = 3.34m<sup>2</sup>



4200g/m<sup>2</sup>



**GENERAL PERFORMANCE**  
EN 649



**REACTION TO FIRE**  
EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m<sup>2</sup>  
EN ISO 11925-2 Pass  
ASTM E648 Class 1



**SLIP RESISTANCE**  
EN 13893 Class DS (dry condition)\*  
AS/NZS 4586 R9



**LIGHT FASTNESS**  
ISO 105-B02 Method 3 ≥6



**ABRASION RESISTANCE**  
EN 649 Group T



**INDENTATION - RESIDUAL**  
EN 433 ≤ 0.1mm



**DIMENSIONAL STABILITY**  
EN 434 ≤ 0.25% max.



**CASTOR CHAIR (continuous use)**  
Suitable



**THERMAL CONDUCTIVITY**  
Suitable for underfloor heating Max. 27°C



**ENVIRONMENTALLY PREFERABLE FLOORING**  
Polyflor Bevel Line PU achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429) in major use areas such as education, healthcare and retail. Bevel Line PU is 100% recyclable and contains 15% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at [www.polyflor.com/environment](http://www.polyflor.com/environment)



**APPLICATIONS**  
Bevel Line is ideal for all residential areas and heavy commercial areas such as hotels, offices, schools, hospitals, airports and department stores.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).  
At the date of issue the data presented is correct.  
\* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

*James Halstead*  
FLOORING



2006




**BEVEL**line™  
THE WOOD & STONE COLLECTION

STONE

PERFORMANCE AND  
PROPERTIES

**A+BRE**  
ENP 429  
ENVIRONMENTAL  
RATING  
Refer to BRE Global ratings  
on [www.greenbooklive.com](http://www.greenbooklive.com)



**POLYFLOR**™  
COVERING THE WORLD